




# Trifold 3-Panel N95 & P2 Respirator

PrimeOn N95 & P2 Respirators are designed to protect against droplet and airborne pathogens and meet the stringent specifications of AS/NZS 1716-2012 Class P2 and NIOSH N95. The Trifold/3-Panel Respirator is divided between top, middle and bottom sections, this design is compact in size for storage and portability, is collapseresistant with extended use while still offering excellent filtration performance and facial-fit, available in two headstrap elastic strengths: Standard-Fit or Relaxed-Fit.



#### Inner Laver

Fluid repellent and antiallergic inner layer to prevent bacterial growth

#### Meltblown Filter

Meltblown layer for bacterial and particle filtration

# Fluid Repellent Filter

Fluid repellent non-woven layer to prevent the risk of contamination

# **Outer Layer**

Additional Fluid repellent material as the first barrier from the outside

PrimeOn Trifold 3-Panel N95 & P2 Respirator	
Number of Fabric Layers	4
Anti-fog Foam	Yes
Latex Free	Yes
Colour	FPR10UN: White w/Blue Headstraps FPR11UN: White w/White Headstraps
Australian/NZ Standard AS/NZS 1716-2012 classification	Class P2
NIOSH	N95
Maximum Total Inward Leakage (TIL)	≤ 8%
Particulate Filtration Efficiency (PFE)	≥ 95%
Maximum Pressure Drop: Inhalation/Exhalation	Inhalation: ≤ 70 Pa (@ 30 L/min) ≤ 240 Pa (@ 95 L/min) Exhalation: ≤ 120 Pa (@ 85 L/min)

### REORDER CODE

FPR10UN Standard-fit Headstraps FPR11UN Comfort-fit Headstraps

# STANDARDS

Australian/NZ Standard AS/NZS 1716-2012 classification, NIOSH N95

### **RECOMMENDED USE**

Where exposure to droplet and/or airborne pathogen is likely

## **PACKAGING**

20 masks per box 28 boxes per carton

MANUFACTURING ACCREDITATIONS ISO 13485









